



Available Access Packages: These packages offer easy interior access to tools and cargo. Each includes three exterior, remote-release, side-access panels that can be opened by Remote Keyless Entry. Not available with optional driver-side 60/40 swing-out doors or sliding passenger-side door.



Compressed Natural Gas (CNG) option: Express 2500 and 3500 Cargo Vans with the CNG option are available with a 3-tank or 4-tank system. The 3-tank system provides a range of up to approximately 200 miles,⁹ while the 4-tank system provides a range of up to 300 miles.⁹ A 5-year/100,000-mile transferable Powertrain Limited Warranty¹⁰ is offered on Express Cargo Vans with CNG.

¹ E85 is a combination of 85% ethanol and 15% gasoline. Go to chevrolet.com/biofuels to see if there is an E85 fuel station near you. ² Requires available Vortec 5.3L V8 engine. ³ Standard with Vortec 4.3L V6 engine. ⁴ Standard with Duramax 6.6L Turbo-Diesel V8 engine. ⁵ Requires available Duramax 6.6L Turbo-Diesel V8 engine and air conditioning. ⁶ Requires Vortec 6.0L V8 engine and available Ambulance Package. ⁷ Cold-cranking amps. ⁸ Duramax 6.6L Turbo-Diesel V8 engine comes with standard dual 770-cca batteries. ⁹ Estimated range based on GM testing and maximum tank capacity. Your range may be less. ¹⁰ Whichever comes first. See dealer for details.

It isn't just a van, it's how you work. And you work with the right tools for the job.

CLASS-LEADING POWERTRAIN CHOICES

Express Cargo Van offers an unmatched selection of engines. Choose the fuel-conscious Vortec 4.3L V6 with an EPA-estimated 19 MPG highway, or select from an extensive lineup of Vortec V8 powerplants – all the way up to the Duramax 6.6L Turbo-Diesel V8, the most

powerful diesel in its class. A standard Hydra-Matic 6-speed automatic transmission on 2500 and 3500 models includes Tap-Up/Tap-Down Driver Shift Control and auto grade braking. Power windows and power door locks are now standard on all models.

GAS, DIESEL, E85 OR CNG Cargo Vans offer a variety of fuel options. Choose from models powered by gasoline, diesel (with the available

Duramax Turbo-Diesel V8) or compressed natural gas (CNG). The available Vortec 5.3L and 6.0L engines can operate on either regular unleaded gasoline, E85¹ – a blend of 85% ethanol and 15% gasoline – or a combination of both. See chevrolet.com for more information. For even more versatility, a 5-passenger Crew Van is a new configuration for 2014.

EXPRESS CARGO VAN SELECT SPECIFICATIONS

| | ■ STANDARD | | □ AVAILABLE | | – NOT AVAILABLE | | | |
|--|------------|----------------------|----------------|--------------|-----------------|----------------|----------------|----------------|
| ENGINE AVAILABILITY | HP @ RPM | LB.-FT. TORQUE @ RPM | 1500 | 1500 AWD | 2500 | 2500 EXT | 3500 | 3500 EXT |
| Vortec 4.3L V6 | 195 @ 4600 | 260 @ 2800 | ■ | – | – | – | – | – |
| Vortec 4.8L V8 | 285 @ 5400 | 295 @ 4600 | – | – | ■ | ■ | ■ | ■ |
| Vortec 5.3L FlexFuel ¹ V8 | 310 @ 5200 | 334 @ 4500 | □ | ■ | – | – | – | – |
| Vortec 6.0L FlexFuel ¹ V8 | 342 @ 5400 | 373 @ 4400 | – | – | □ | □ | □ | □ |
| Vortec 6.0L V8 (CNG) | 279 @ 4700 | 320 @ 4400 | – | – | □ | □ | □ | □ |
| Duramax 6.6L Turbo-Diesel V8 | 260 @ 3100 | 525 @ 1600 | – | – | □ | □ | □ | □ |
| TRANSMISSION/TRANSFER CASE AVAILABILITY | | | 1500 | 1500 AWD | 2500 | 2500 EXT | 3500 | 3500 EXT |
| Hydra-Matic 4-speed automatic with overdrive and Tow/Haul mode | | | ■ | ■ | – | – | – | – |
| Hydra-Matic 6-speed automatic with overdrive, Tap-Up/Tap-Down Driver Shift Control, auto grade braking and Tow/Haul mode | | | – | – | ■ | ■ | ■ | ■ |
| CHASSIS FEATURES | | | 1500 | 1500 AWD | 2500 | 2500 EXT | 3500 | 3500 EXT |
| Alternator: 125-amp | | | □ ² | ■ | – | – | – | – |
| 145-amp | | | ■ ³ | – | □ ⁴ | □ ⁴ | □ ⁴ | □ ⁴ |
| 105-amp | | | – | – | ■ | ■ | ■ | ■ |
| Dual 145-amp ⁵ | | | – | – | □ | □ | □ | □ |
| 160-amp ⁶ | | | – | – | – | – | – | □ |
| Battery: 600-cca ⁷ | | | ■ | ■ | ■ | ■ | ■ | ■ |
| High-capacity 770-cca ⁷ | | | □ | □ | □ ⁸ | □ ⁸ | □ ⁸ | □ ⁸ |
| Brakes: Power, hydraulic 4-wheel ventilated disc | | | ■ | ■ | ■ | ■ | ■ | ■ |
| 4-wheel antilock with Dynamic Rear Proportioning | | | ■ | ■ | ■ | ■ | ■ | ■ |
| Front rotor diameter and thickness | | | 12.0" x 1.1" | 12.0" x 1.1" | 12.8" x 1.5" | 12.8" x 1.5" | 12.8" x 1.5" | 12.8" x 1.5" |
| Rear rotor diameter and thickness | | | 13.0" x 1.2" | 13.0" x 1.2" | 13.0" x 1.1" | 13.0" x 1.1" | 13.0" x 1.1" | 13.0" x 1.1" |
| Differential: Automatic locking rear | | | □ | □ | □ | □ | □ | □ |
| Front Gross Axle Weight Rating | | | 3,600 lbs. | 3,700 lbs. | 4,100 lbs. | 4,300 lbs. | 4,600 lbs. | 4,600 lbs. |
| Rear Gross Axle Weight Rating | | | 4,000 lbs. | 4,000 lbs. | 5,360 lbs. | 5,360 lbs. | 6,084 lbs. | 6,084 lbs. |



NOTHING POWERS UP LIKE CHEVY EXPRESS

Express Cargo Van 1500 AWD in Summit White with available features.

EXPRESS PASSENGER VAN: IT'S A SURE THING



Express 3500 LS Extended Wheelbase Passenger Van in Silver Ice Metallic with available features.

When you're transporting people for a living, safety is paramount. The Chevy Express Passenger Van offers standard safety features such as head-curtain side-impact air bags,¹ the StabiliTrak Electronic Stability Control System, a Tire Pressure Monitoring System (except spare tire) and antilock

brakes. Enhanced Technology Glass (ETG)² for a quiet ride is standard on 12- and 15-passenger models. And you can easily tailor the Express Van to your exact needs with a choice of 8-, 12- and 15-passenger seating configurations, depending on model.

REAR VISION CAMERA AND REAR PARK ASSIST
An available integral rear vision camera and Rear Park Assist help you detect certain stationary objects located behind the vehicle when traveling in reverse at low speeds.



Mobility vehicles: We want to make it easier and safer for people with special needs (and those who care for them) to travel. Express provides abundant interior space and accessibility that wheelchair and scooter users appreciate. Express is a practical choice for mobility and paratransit conversions. It's designed to allow easy installation of adaptive equipment and mobility accessories like wheelchair lifts, ramps, running boards and driver aids, available from independent aftermarket suppliers.⁵

EXPRESS PASSENGER VAN SELECT SPECIFICATIONS

| ENGINE AVAILABILITY | HP @ RPM | LB.-FT. TORQUE @ RPM | ■ STANDARD □ AVAILABLE – NOT AVAILABLE | | | | |
|--------------------------------------|------------|----------------------|--|----------|------|------|----------|
| | | | 1500 | 1500 AWD | 2500 | 3500 | 3500 EXT |
| Vortec 5.3L FlexFuel ³ V8 | 310 @ 5200 | 334 @ 4500 | ■ | ■ | – | – | – |
| Vortec 4.8L V8 | 285 @ 5400 | 295 @ 4600 | – | – | ■ | ■ | ■ |
| Vortec 6.0L FlexFuel ³ V8 | 342 @ 5400 | 373 @ 4400 | – | – | □ | □ | □ |
| Duramax 6.6L Turbo-Diesel V8 | 260 @ 3100 | 525 @ 1600 | – | – | – | □ | □ |

| TRANSMISSION/TRANSFER CASE AVAILABILITY | 1500 | 1500 AWD | 2500 | 3500 | 3500 EXT |
|--|------|----------|------|------|----------|
| Hydra-Matic 4-speed automatic with overdrive and Tow/Haul mode | ■ | ■ | – | – | – |
| Hydra-Matic 6-speed automatic with overdrive, Tap-Up/Tap-Down Driver Shift Control, auto grade braking and Tow/Haul mode | – | – | ■ | ■ | ■ |

| CHASSIS FEATURES | 1500 | 1500 AWD | 2500 | 3500 | 3500 EXT |
|--|----------------|----------------|----------------|----------------|--------------|
| All-Wheel Drive (AWD) | – | ■ | – | – | – |
| Alternator: 105-amp | – | – | ■ | ■ | – |
| 125-amp | ■ | ■ | – | – | – |
| 145-amp | □ ⁴ | □ ⁴ | □ ⁴ | □ ⁴ | ■ |
| Brakes: Power, hydraulic 4-wheel ventilated disc | ■ | ■ | ■ | ■ | ■ |
| 4-wheel antilock with Dynamic Rear Proportioning | ■ | ■ | ■ | ■ | ■ |
| Front rotor diameter and thickness | 12.0" x 1.1" | 12.0" x 1.1" | 12.8" x 1.5" | 12.8" x 1.5" | 12.8" x 1.5" |
| Rear rotor diameter and thickness | 13.0" x 1.2" | 13.0" x 1.2" | 13.0" x 1.1" | 13.0" x 1.1" | 13.0" x 1.1" |
| Oil-Life Monitor | ■ | ■ | ■ | ■ | ■ |
| StabiliTrak Electronic Stability Control System | ■ | ■ | ■ | ■ | ■ |
| Steering: Power | ■ | ■ | ■ | ■ | ■ |
| Front Gross Axle Weight Rating | 3,600 lbs. | 3,700 lbs. | 4,100 lbs. | 4,600 lbs. | 4,600 lbs. |
| Rear Gross Axle Weight Rating | 4,000 lbs. | 4,000 lbs. | 5,360 lbs. | 6,084 lbs. | 6,084 lbs. |

¹ Always use safety belts and the correct restraint for your child's age and size. Even in vehicles equipped with the Passenger Sensing System, children are safer when properly secured in a rear seat in the appropriate infant, child or booster seat. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with a passenger air bag. See the Owner's Manual and the child safety seat instructions for more safety information. ² ETG is part of the overall occupant protection system on Passenger Vans. ETG may help keep passengers sitting next to these windows from being ejected through the glass in some, but not all, crashes. Even with this glass, safety belts must be worn at all times. For Passenger Vans, use only ETG glass approved for your vehicle for replacement when damaged. ³ E85 is a combination of 85% ethanol and 15% gasoline. Go to chevrolet.com/biofuels to see if there is an E85 fuel station near you. ⁴ Requires available rear air conditioning. Standard on LT trim level. ⁵ GM is not responsible for the safety or quality of design features, materials or workmanship of any alterations by such a supplier. ⁶ Visit onstar.com for details and system limitations.



With OnStar,[®] experience the safe, simple way to stay connected on the road. OnStar is now standard on all Passenger Van models – available on Cargo Van and Commercial Cutaway models – with the Directions & Connections[®] Plan for the first six months.⁶